



Impact wrench - extra short

Maximum loosening torque: 1100 Nm · Square, solid 12.5 mm (1/2 inch) · Single hammer striking mechanism

Article no.: 9012M

EAN: 4000896188987

Product information

- Maximum loosening torque: 1100 Nm
- **Extremely compact construction enables working in areas with restricted access**
- One-hand operation for right and left handed operators
- Exhaust air is guided through the handle downwards
- Reduced vibrations
- Easy handling
- **Extra short – only 92 mm**
- Single hammer striking mechanism
- Air connection inlet: Inside thread 12.91 mm (1/4")
- Coupler plug: Nominal size 7.2 (included)
- Recommended torque: 610 Nm
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 108.1 db(A) Lp W
- Vibration acceleration: 9.57 m/s²
- Loosening torque (max) determined with screw size M: 16
- Forward and reverse: three-stage (forward), single-stage (reverse)
- Cold insulated handle
- Output: Square, solid 12.5 mm (1/2 inch)
- Net weight: 1.24 kg
- For impact operation
- Tightening torque max Nm: 678 Nm
- Maximum loosening torque: 1100 Nm
- Sound pressure level: 97.5 dB(A) Lp A
- Revolutions per minute: 10000
- Air requirement: 127 l/min (2.1 l/sec)





TECHNICAL DATA

- **Output:** $12\frac{1}{2}$
- **Manual / impact operation:** For impact operation
- **Handle:** Cold insulated handle
- **Sound power level (at working pressure):** 108.1 db(A) Lp W
- **Forward/reverse:** three-stage (forward), single-stage (reverse)
- **Max. loosening torque:** 1100 Nm
- **Recommended torque:** 610 Nm
- **Loosening torque (max) determined with screw size M:** 16 M
- **Striking mechanism (type):** Single hammer striking mechanism
- **Air requirement [l/min]:** 127 l/min
- **Sound pressure level (at working pressure):** 97.5 dB(A) Lp A
- **Tightening strap height:** 678 Nm

